## Metadata

Standardized Instrument Name	METEOROLOGICAL STATIONS
Scheme URI	http://vocab.nerc.ac.uk/collection/P19/current/PLSR0226/
Term URI	SDN:P19::PLSR0226
Instrument DOI	
Instrument Unique ID	30023406813390
ID Type	Serial Number
Model No.	H22-E14, S0H118303
Instrument Type	Baseline
Description	Made up of multiple components listed below. Serial number is Iridium Weather station IMEI Equipment cost: \$9,904.50 + Iridium satellite Premium Plan: \$1,350 Sensor details found in attachment - Instrument Details - HOBO MMF Weather Station 1
Manufacturer	Hoskin Scientific Limited
Manufacturer type	Organizational
Notes	HOBO brand field gear that includes various sensors attached to tripod outfitted with solar panel and battery located in housing box. This meteorological station is located in St. Laurent and is owned by the Manitoba Metic Federation (MMF). Calibration certificates stored in Lab Collector. They can be provided upon request.
Sensor Details	
Sensor Details 1	
Instrument Sensor Name	Temperature and Relative Humidity
Instrument Sensor Serial No.	21048243
Sensor Range	Temperature: -40°C to 75°C (-40°F to 167°F); RH: 0-100% RH at -40° to 75°C (-40° to 167°F); exposure to conditions below -20°C (-4°F) or above 95% RH may temporarily increase the maximum RH sensor error by an additional 1%
Sensor Sensitivity	Temperature: ±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F); RH: ±2.5% from 10% to 90% RH typical to a maximum of ±3.5% including hysteresis at 25°C (77°F); below 10% and above 90% ±5% typical

**Sensor Units** °C and %

**Last Calibration** 

Date

**Sensor Details 2** 

Instrument **Sensor Name** 

Photosynthetically Active Radiation (PAR)

Instrument

**Sensor Serial** 

21040570

No.

**Sensor Range** 0 to 2500 µmol/m2/sec, wavelengths 400 to 700 nm

Sensor Sensitivity  $\pm 5\ \mu mol/m2/sec$  or  $\pm$  5%, whichever is greater in sunlight; additional temperature induced

error ±0.75 µmol/m2/sec/°C from 25°C (0.42 µmol/m2/sec/°F from 77°F)

**Sensor Units** µmol/m2/sec

**Last Calibration** 

**Date** 

**Sensor Details 3** 

Instrument **Sensor Name** 

**Barometric Pressure** 

Instrument

**Sensor Serial** 

No.

20812842

**Sensor Range** Rated for -40C to +70C, must be used inside logger case, w/ 10 cm cable

Sensor Sensitivity ±3.0 mbar (0.088 in. Hg) over full pressure range at 25°C (77°F); maximum error of ±5.0

mbar (0.148 in. Hg) over -40° to 70°C (-40° to 158°F)

**Sensor Units** mbar

**Last Calibration** 

**Date** 

**Sensor Details 4** 

Instrument **Sensor Name** 

Wind sensor/monitor

Instrument

**Sensor Serial** 

No.

21055171

**Sensor Range** S-WCB-M003: 0 to 50 m/s (0 to 112 mph)

Sensor Sensitivity

0.20 m/s (0.46 mph) and 1.4 degrees

**Sensor Units** m/s and degrees

**Last Calibration** 

**Date** 

**Sensor Details 5** 

Instrument Sensor Name

Rain Gauge

Instrument

**Sensor Serial** 

21050257

No.

Sensor Range

0 to 12.7 cm (0 to 5 in.) per hour, maximum 4000 tips per logging interval

Sensor Sensitivity

0.01 in. (S-RGA-M002) or 0.2 mm (S-RGB-M002)

Sensor Units

mm

**Last Calibration** 

Date

## **Related Datasets**

Title St Laurent Li Taan Aen Staansyoon

URL <a href="https://lwbin-dev.ad.umanitoba.ca/data/fr/dataset/met-1-data">https://lwbin-dev.ad.umanitoba.ca/data/fr/dataset/met-1-data</a>